

LIS007359888B2

(12) United States Patent Snider

(10) Patent No.: US 7,359,888 B2 (45) Date of Patent: *Apr. 15, 2008

(54) MOLECULAR-JUNCTION-NANOWIRE-CROSSBAR-BASED NEURAL NETWORK

- (75) Inventor: Greg Snider, Mountain View, CA (US)
- (73) Assignee: **Hewlett-Packard Development Company, L.P.**, Houston, TX (US)
- (*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 724 days.

This patent is subject to a terminal dis-

claimer.

- (21) Appl. No.: 10/355,801
- (22) Filed: Jan. 31, 2003

(65) Prior Publication Data

US 2004/0150010 A1 Aug. 5, 2004

(51) Int. Cl.

G06E 1/00 (2006.01)

G06E 3/00 (2006.01)

G06F 15/18 (2006.01)

G06G 7/00 (2006.01)

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

2,835,829 A	*	5/1958	Chollet et al	327/487
4,823,174 A	*	4/1989	Itoh et al	257/198

6,128,214 A	* 10/2000	Kuekes et al 365/151
6,314,019 B1	11/2001	Kuekes et al.
6,735,579 B1	\$ 5/2004	Woodall 706/20
6,889,216 B2	5/2005	Nugent
2003/0200521 A13	* 10/2003	DeHon et al 716/16
2003/0236760 A13	* 12/2003	Nugent 706/26
2004/0039717 A1	2/2004	Nugent

OTHER PUBLICATIONS

3/2004 Snider et al. 327/365

Gudiksen, Mark S., et al., "Growth of nanowire superlattice structures for nanoscale photonics and electronics", Nature, vol. 415, Feb. 7, 2002.

* cited by examiner

2004/0041617 A1*

Primary Examiner—Joseph P Hirl

(57) ABSTRACT

A method for configuring nanoscale neural network circuits using molecular-junction-nanowire crossbars, and nanoscale neural networks produced by this method. Summing of weighted inputs within a neural-network node is implemented using variable-resistance resistors selectively configured at molecular-junction-nanowire-crossbar junctions. Thresholding functions for neural network nodes are implemented using pFET and nFET components selectively configured at molecular-junction-nanowire-crossbar junctions to provide an inverter. The output of one level of neural network nodes is directed, through selectively configured connections, to the resistor elements of a second level of neural network nodes via circuits created in the molecularjunction-nanowire crossbar. An arbitrary number of inputs, outputs, neural network node levels, nodes, weighting functions, and thresholding functions for any desired neural network are readily obtained by the methods of the present invention.

17 Claims, 17 Drawing Sheets

